

CPC375V

IR Camera

● Product Overview

Equipped with a 1/3" SONY Super HAD color CCD image sensor, this IR camera has satisfactory minimum illumination of 0.5 Lux / F2.0 to provide clear and sharp images to consolidate the safety of your surveillance environment.



● Features

- Fine Image: 1/3" SONY Super HAD color CCD image sensor to provide clear pictures
- Satisfied Min. Illumination: 0.5 Lux / F2.0; 0 Lux (15 meter IR ON)
- IR LED: 24 units
- Effective Range: Over 15 Meters
- Water & Dust Resistance: IP68

● Specification

	CPC375V
Pick up Element	1/3" SONY Super HAD Color CCD image sensor
Number of Pixels	510(H) x 492(V)<NTSC>/ 500(H) x 582(V)<PAL>
Resolution	Standard
Min. Illumination	0.5 Lux / F2.0; 0 Lux (IR ON)
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 second
Lens	f3.6mm/F2.0; f6.0mm/F2.0
Lens Angle	92.6° / 54°
Iris Mode	AES
AGC	AUTO
White Balance	ATW
Video Output	1.0Vp-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption	90mA (IR OFF), 330mA (IR ON)
Water & Dust Resistance	IP68
IR LED	24 units
Effective Range	Over 15 Meters
Dimension (mm)	100(L) × 65(W) × 63.8(H)

* The specifications are subject to change without notice.